



# Electric/Hydraulic Spreader Control

SAM™ remote electronic spreader control systems provide reliable control of hydraulic spreader valves for convenient in cab operation. The remote electronic cab controller eliminates cab noise and cumbersome hydraulic plumbing by locating the hydraulic spreader valve outside the cab.

**Model HV715EP**

- 7 GPM Proportional spinner cartridge.
- 15 GPM Proportional auger-conveyor cartridge

**Model HV1030EP**

- 10 GPM Proportional spinner cartridge.
- 30 GPM Proportional auger-conveyor cartridge.

**Package Includes**

- 12V programmable cab controller with detented auger-conveyor/spinner controls
- Dual LED, displays valve settings
- Momentary auger-conveyor blast button (Adjustable duration)
- Two wire harnesses w/Weather Pac connectors
- Electric/Hydraulic spreader valve (anodized)
- Poly "Top Hat" sealed enclosure 8-3/4 Diameter x 9" High
- Powder coated steel frame mounting bracket. SAE Ports, 3,000 PSI

***In Stock for Immediate Shipping!***

PART NO.	DESCRIPTION	PRODUCT CATEGORY	WT.
<b>HV715E</b>	Electric Spreader Valve, 22 GPM Total Valve Flow	902	8.00 lbs.
<b>HV1030E</b>	Electric Spreader Valve, 40 GPM Total Valve Flow	902	8.12 lbs.
<b>HVB</b>	Valve Box	902	3.02 lbs.
<b>HVC05</b>	Controller	902	2.01 lbs.
<b>HVH15</b>	Wire Harness, 15'	902	1.02 lbs.
<b>HVH8</b>	Wire Harness, 8'	902	0.08 lbs.
<b>3016035</b>	Bracket	902	8.50 lbs.
<b>HV715EP</b>	Elec-Hyd Spreader Valve Kit (7 GPM Spinner/15 GPM Auger-Conv.)	902	30.0 lbs.
<b>HV1030EP</b>	Elec-Hyd Spreader Valve Kit (10 GPM Spinner/30 GPM Auger-Conv.)	902	30.0 lbs.

Pricing is consistent with current market conditions and is subject to change without notice.