

SnowDogg

by **Buyers**



TECHNICAL SERVICE BULLETIN

NUMBER	TSB16-23	TYPE	INSTALLATION ALERT		
TITLE	TOYOTA TUNDRA NON-DRL LIGHT WIRING				
REV	A	ISSUED	9/4/2009	REVISED	-
AFFECTS	2001-2006 TOYOTA TUNDRA'S WITHOUT DRL'S TUNDRAS WITH DRL'S ARE NOT AFFECTED				
INFORMATION	THE AFFECTED APPLICATIONS HAVE A DIFFERENT LIGHTING CIRCUIT THAN THOSE WITH DRLS, AND MUST BE WIRED USING THE "SWITCHED GROUND" CONFIGURATION				
IDENTIFICATION	THE AFFECTED APPLICATIONS WILL HAVE A RED WIRE WITH A YELLOW STRIPE ON THE CENTER PIN OF THE HEADLIGHT CONNECTOR				
INSTRUCTIONS	<p>The RELAY HARNESS must be installed for SWITCHED GROUND configuration.</p> <ul style="list-style-type: none"> - Locate the gray wire with male/female (already connected). Disconnect the two halves. The male quick connect end of the gray wire will not be used and may be taped off. - The female end should be connected to the RED/WHITE wire from the 16160300 harness. - Connect the other wires as shown - Connect brown wire to ground. <div style="text-align: center;"> <p>SWITCHED GROUND HEADLIGHTS (SEE APP GUIDE FOR ASSISTANCE)</p> </div> <p><i>Instructions For Use With 16160100/B Relay Harness. Contact SnowDogg Tech Support At 866-974-3644 For Use With Earlier Harnesses.</i></p>				